



KEEP OUT OF REACH OF CHILDREN

Green Lawnger[®]

Turf paint and divot mix colourant

A permanent green paint for turf use

- Adds healthy appearance to warm – and cool – season turf grasses
 - Will not wash off or wear off turf
 - Application on dormant turf lasts through winter
 - Non-phytotoxic to turf
- Recommended for athletic fields, golf courses, commercial and residential lawns

CONTENTS: 10L

BASF Australia Ltd ABN 62 008 437 867
Level 12, 28 Freshwater Place Southbank VICTORIA 3006, AUSTRALIA
Website: www.agro.basf.com.au

BASF New Zealand Ltd 110297
Level 4, 4 Leonard Isitt Drive, Auckland Airport, AUCKLAND, 2022, NEW ZEALAND
Website: www.agro.basf.com.nz

™ Trademark of BASF

DIRECTIONS FOR USE

Before applying Green Lawnnger®, mow turf area to desired height. 1L of Green Lawnnger covers between 100 and 300m² of turf. The wide coverage range is due to the type of condition of grass being treated, and turf colour desired.

For fall application on dormant turf, dilute 1L of Green Lawnnger® with 7 to 9 L of water. For a darker colour, a lower volume of water is recommended. Some experimentation may be required with ratios.

For summer application on discoloured turf, dilute 1L with 15 to 20 L of water. Rate depends on desired colour. For best results on discoloured areas, two applications are recommended to blend the applied area with the existing healthy turf.

EQUIPMENT NOTICE

BASF recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawnnger® in centrifugal pumps. Standard ceramic seals may leak during operation. A spray shield is recommended for application if overspray or drift is a potential problem. Avoid overspray on concrete, masonry, or any other objects where colour is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent rub-off on uniforms, allow Green Lawnnger to dry prior to using athletic field. Rinse spray tank. Spray nozzles, and screens thoroughly with water immediately following use. For best results, use low to medium sprayer pressure.

DIVOT MIX SAND

Mix 200mL of Green Lawnnger with the same volume of water. Spray or pour the solution onto 50kg of divot mix sand in a cement-type mixer.

PRECAUTIONS

Keep out of reach of children. Avoid contact with the eyes and skin. See SDS for further information.

This product does not require a hazard warning label in accordance with GHS criteria.

CONDITIONS OF SALE

All conditions and warranties rights and remedies implied by law or arising in contract or tort whether due to the negligence of BASF Australia Ltd ABN 62008437867 or otherwise are hereby expressly excluded so far as the same may legally be done provided however that any rights of the Buyer pursuant to non excludable conditions or warranties of the Competition and Consumer Act 2010 or any relevant legislation of any State are expressly preserved but the liability of BASF Australia Ltd or any intermediate Seller pursuant thereto shall be limited if so permitted by the said legislation to the replacement of the goods sold or the supply of equivalent goods and all liability for indirect or consequential loss or damage of whatsoever nature is expressly excluded. This product must be used or applied strictly in accordance with the instructions appearing hereon. This product is solely sold for use in Australia and must not be exported without the prior written consent of BASF Australia Ltd.

Batch No:

Date of Manufacture:

BASF Australia Ltd
ABN 62 008 437 867
Level 12, 28 Freshwater Place
Southbank VICTORIA 3006
AUSTRALIA

FOR SPECIALIST ADVICE IN AN EMERGENCY ONLY PHONE 1800 803 440 TOLL FREE – ALL HOURS – AUSTRALIA WIDE

BASF New Zealand Ltd
110297

Level 4, 4 Leonard Isitt Drive
Auckland Airport AUCKLAND 2022
NEW ZEALAND

EMERGENCY PHONELINK 0800 944 955 TOLL FREE – ALL HOURS – NEW ZEALAND WIDE

